

PSA Tapes Corp

Panamá Pacífico
Panamá

SPECIFICATION DATA SHEET

Date of issue / review : 14/2/2017

REF: BOPP-CG

Product: BOPP TAPE WITH NATURAL RUBBER ADHESIVE

Application: General and extra strong use
Especially recommended to achieve immediate and permanent adhesion
Resistant to acid and alkaline thinners.
Resistant to temperatures up to -30 ° C if applied at room temperature.
Resistant to temperatures up to + 130 ° C for short periods of exposure.

Substrate: Bioriented Polypropylene
Adhesive: Natural rubber in solvent base

Colors: Transparent and Brown

Dimensions: Widths of 18 mm, 24 mm and 48 mm / Lengths from 20 m to 600 m, depending on the width.

			Options
Total thickness (ASTM D 3652)	Unit micras	Tolerance ± 10%	44
Substrate thickness (ASTM D 3652)	micras		25
Peel adhesion (ASTM D 3330)	N/cm		>2
Tensile Strength (ASTM D 3759)	N/cm		>36
Elongation (ASTM D3759)	%		130
Initial Tack (ASTM D 3121)	mm		13
Application Temperature Range	C		From 2 to 45
Operational Temperature Range	C		From -25 to 65

(Min = minimum value obtained from a series of batch tests)

Storage conditions:

Store in a clean and dry place.

Temperatures of 25 ° ± 2 ° C and relative humidity in the range of 55% ± 5% are recommended.

All values are presented for comparative purposes and do not represent manufacturer's guarantee.

It is suggested to the buyer to verify, before using, the suitability of this product for the particular application