

SPECIFICATION DATA SHEET

Date of issue / review :

10/7/2018

REF:

DA-BOPP

Product:

DOBLE-SIDED OPP TAPE

Application: Double general purpose adhesive suitable for fixing carpets and carpets.
Suitable for light assemblies, fixing and joining sheets of paper and fabrics.
High initial adhesion

Substrate: Bioriented polypropylene carrier with siliconized paper protector
Adhesive: Transparent

Dimensions: Widths of 18 mm, 24 mm and 48 mm / Lengths from 20 m to 150 m, depending on width
Other widths for special orders

	Unit	Tolerance	Options	
			MEDIUM	PREMIUM
Total thickness (ASTM D 3652)	micras	± 6	85	100
Peel adhesion (ASTM D 3330)	N/cm	± 2	9	4
Tensile Strength (ASTM D 3759)	N/cm	± 10	40	27
Elongation (ASTM D3759)	%	±25	150	80
ADHESIVE			HotMelt	Acrilico Xtra

(Min = minimum value obtained from a series of batch tests)

Storage conditions:

Store in a clean and dry place.

Temperatures of 25 ° ± 2 ° C and relative humidity in the range of 55% ± 5% are recommended.

All values are presented for comparative purposes and do not represent manufacturer's guarantee.

It is suggested to the buyer to verify, before using, the suitability of this product for the particular application