

# PSA Tapes Corp

Panamá Pacífico  
Panamá

## SPECIFICATION DATA SHEET

Date of issue / review : 31/7/2018

REF: **DUCT-G**

**Product:** *DUCT TAPE FOR GENERAL USE*

**Application:** To pack, unite, repair, temporarily fix in general activities.  
HVAC applications, gasket material, general maintenance  
Easy manual cutting.

**Substrate:** Polyethylene reinforced with polyester fabric.

**Adhesive:** Natural rubber adhesive

**Colors** Silver grey

**Dimensions:** Widths of 18 mm, 24 mm and 48 mm / Lengths from 9 m to 60 m, depending on width

	Unit	Tolerance	Options
			MEDIUM
<b>Total thickness (ASTM D 3652)</b>	micras	± 15	<b>280</b>
<b>Peel adhesion (ASTM D 3330)</b>	N/cm	± 1	8,76
<b>Tensile Strength (ASTM D 3759)</b>	N/cm	± 10	38,52
<b>Elongation (ASTM D3759)</b>	%	±10	122
<b>Application Temperature Range</b>	°C		From +4 to +32
<b>Operational Temperature Range</b>	°C		From 0 to +82

(Min = minimum value obtained from a series of batch tests)

**Storage conditions:**

Store in a clean and dry place.

Temperatures of 25 ° ± 2 ° C and relative humidity in the range of 55% ± 5% are recommended.

All values are presented for comparative purposes and do not represent manufacturer's guarantee.

It is suggested to the buyer to verify, before using, the suitability of this product for the particular application