

PSA Tapes Corp

Panamá Pacífico
Panamá

SPECIFICATION DATA SHEET

Date of issue / review : 31/7/2018

REF: DUCT-UV

Product: EXTRA STRONG DUCT TAPE FOR EXTERIOR USE

Application: To join, repair, temporarily fix in workshops, boats, construction
Weather resistant for 7 days once applied
Easy manual cutting. Does not leave adhesive residue

Substrate: Complex of high thickness orange polyethylene film with high resistance mesh

Adhesive: Adhesive with synthetic rubber base and modified hydrocarbon resins for weather resistance

Colors Orange

Dimensions: Widths of 18 mm, 24 mm and 48 mm / Lengths from 9 m to 60 m, depending on width

Options			
	Unit	Tolerance	
Total thickness (ASTM D 3652)	micras	± 15	235
Substrate thickness (ASTM D 3652)	micras	± 4	80
Peel adhesion (ASTM D 3330)	N/cm	± 1,5	11,5
Tensile Strength (ASTM D 3759)	N/cm	± 5	45
Elongation (ASTM D3759)	%	±2,5	117,5

(Min = minimum value obtained from a series of batch tests)

Storage conditions:

Store in a clean and dry place.

Temperatures of 25 ° ± 2 ° C and relative humidity in the range of 55% ± 5% are recommended.

All values are presented for comparative purposes and do not represent manufacturer's guarantee.

It is suggested to the buyer to verify, before using, the suitability of this product for the particular application